



REQUEST A QUOTE

Attenuators



SPECIFICATION	
Return Loss	≥-55dB (UPC) ≥-65dB (APC)
Attenuation Tolerance	1 to 10dB : ±0.5, 11 to 30 dB : ±5%
Operational Wavelengths	1310 and 1550nm
Operating Temperature	-40 to +75°C

\$17.95



CONNECTOR		TYPE		ATTENUATION LEVEL		ATTENUATION TOLERANCE	
DFA	Dope Fiber Attenuators	432	SC APC	01	1dB	1	Premium
		532	FC APC	02	2dB		
		632	SC UPC	03	3dB		
		732	FC UPC	04	4dB		
		832	ST UPC	05	5dB		
		1332	MU SPC	06	6dB		
		1432	MU UPC	07	7dB		
		1532	LC UPC	08	8dB		
		1632	LC APC	09	9dB		
				10	10dB		
				12	12dB		
				15	15dB		
				20	20dB		
				25	25dB		

DFA - 632 - 04 - 1

Bulk-Head Attenuators

Bulkhead Attenuators utilize a wavelength sensitive neutral density filter to achieve attenuation. Available in 5, 10, 15 and 20dB values. Select from 1310nm or 1550nm options.



\$14.95

STYLE	CONNECTOR	WAVE LENGTH	ATTENUATION LEVEL
F18	BH Attenuator	12 ST UPC	3 1310 1 5dB
		22 FC UPC	5 1550 2 10dB
		32 SC UPC	3 15dB
			4 20dB

F18 - 12 - 53