


16-Fiber Optic Termination Box

2 Input Ports at 20mm

Overview

Fibertronics Inc. offers a variety of fiber optic termination boxes engineered to securely house and organize fiber splices, connectors, and pigtails. Suitable for a wide range of applications—including telecommunications, data centers, and network equipment rooms—these enclosures provide a protected environment that ensures stable performance and simplifies cable management. With durable construction and user-friendly features, our termination boxes support efficient fiber distribution, minimize signal loss, and promote long-term system reliability.



Features

- Wall-mountable or pole-mountable
- Easy installation and maintenance
- Bend radius protection for fiber cables
- Integrated splice trays for fiber management
- Durable, weather-resistant construction

Applications

- FTTH and FTTB installations
- Data centers and server rooms
- Telecommunications and broadband networks
- Enterprise LAN/WAN infrastructures
- Outdoor/indoor building entry points

Technical Specifications

Ports	2 Input Ports
Splice Capacity	16 Fibers
Cable Diameter	2x Φ 20mm max.
Dimensions	265mm x 155mm x 48mm
Adapter Slots*	Up to 8x SC Simplex -OR- LC Duplex
Housing Material	Cold Rolled Steel
Accessories	Wall Mount Kit

*Accepts both flanged and non-flanged adapters (sold separately)