

48-Fiber Outdoor Horizontal Splice Closure

2 Splice Trays Included - 4 Ports at 16mm - 48 Fiber Max Capacity

Overview

Fibertronics Inc. offers horizontal splice closures designed to protect and manage spliced fiber optic cables in a variety of network environments. These closures provide a sealed, durable housing that shields fiber splices from moisture, dust, and extreme temperatures. Suitable for aerial, underground, and direct-burial applications, they are built to ensure long-term reliability in harsh conditions. Fibertronics' designs also support easy installation and high fiber capacity, making them ideal for both small and large-scale fiber networks.



Key Features

- All performance indicators meet GR-771-CORE standards
- Suitable for aerial, wall-mount, or direct burial applications
- IP68 Rated – Dustproof and water-resistant
- Corrosion and UV resistant

Typical Applications

- Underground, aerial, and direct-buried fiber optic splicing
- Outside Plant (OSP) fiber network deployments
- FTTx (FTTH, FTTB, FTTC) rollout and maintenance
- Telecommunications and ISP backbone networks

Technical Specifications

Ports	4 Ports
Splice Capacity	48 Fibers
Splice Tray Capacity	2 Trays
Cable Diameter	Φ16mm max.
Closure Size	420mm x 127mm x 72mm
IP Rating	IP68
Sealing Type	Mechanical
Housing Material	Polypropylene with glass fiber reinforcement
Internal Components Material	ABS
Metal Accessories Material	Stainless Steel